

## Bisphenol A

### 1. Description

Bisphenol A is an important organic chemical raw material with a wide range of uses. It can be used to produce polycarbonate (PC), epoxy resin, polyester resin, polysulfone resin, polyphenylene ether resin, unsaturated polyester resin and other polymer materials.

### 2. Application

- Engineering plastics polycarbonate
- Epoxy resin
- High temperature resistant polyester resin
- Plasticizer

### 3. Product parameters

Test items	Detection index	Units
appearance	White particles	/
<b>Crystallization point</b>	<b>≥156.6</b>	<b>°C</b>
<b>Melting color ( 157 °C )</b>	<b>≤20</b>	<b>Hazen</b>
<b>Solution color (CH<sub>3</sub>OH)</b>	<b>≤10</b>	<b>Hazen</b>
<b>Purity of bisphenol</b>	<b>≥99.85</b>	<b>%</b>



<b>A</b>		
<b>Phenol content</b>	<b>≤50</b>	<b>mg/kg</b>
<b>water content</b>	<b>≤500</b>	<b>mg/kg</b>

#### 4. Product packaging

This product is packed and transported in 25 kg net per bag

Other packaging can be provided on request.

#### 5. Storage and precautions

- 1). This product should be stored in a cool, dry and ventilated warehouse.
- 2). Keep away from heat source and fire source and avoid direct sunlight.
- 3). The storage life of this product is generally 1 year. If it exceeds the time limit, it should be tested. If it meets the index, it can still be used.

#### Disclaimer

All recommendations for use of our products whether given by us in writing, verbally or to be implied from the results of tests carried out by us are based on the current state of our knowledge. Although, the information contained in this sheet is accurate, no liability can be accepted in respect of such information. We warrant only that our product will meet the designated specifications and make no other warranty either express or implied, including any warranty of merchantability or fitness for a particular.